



NI-VISION

Premium CCTV Brand



NI-IPC-I1ABC ECO-LITE



Automatic ICR



IR Night Vision



Support PoE



Mobile
Monitoring



Multi-Platform
Support



Automatic
Electronic Shutter



Alarm Push
Notification



Support Onvif



Specification

| Camera | |
|--------------------|---|
| Megapixel | 5MP |
| Image Sensor | illumination CMOS sensor |
| Min. Illumination | Color: 0.01Lux @ (F1.2AGC ON): 0 Lux with IR B/W: 0.001Lux @ (F1.2AGC ON): 0 Lux with IR |
| Shutter Speed | 1/50(1/60)s to 1/10,000s |
| Lens | 4mm |
| Day & Night | Warm Light - Full Color Day & Night |
| Network | |
| Storage | Network storage on HDD |
| PoE | Support |
| Protocol | TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP, HTTPS, SIP, 802.1x, IPV6 Option |
| Security Features | Video Loss, Video Blocking, Power Protection, Password Protection |
| Compression | |
| Video Compression | H.265 AI (Compatible H.265/H.264) High Profile, JPEG Snapshot |
| Bite Rate | 0.1 Mbps ~ 8 Mbps |
| Audio Compression | G.711a |
| Interface | |
| Ethernet | 1*10/100 Mbps Ethernet port RJ45 Port |
| Audio Input | Mic |
| Audio Output | Speaker, External Using Audio Wire, No Inbuilt Output Audio |

| Image | |
|-----------------------|--|
| Max. Image Resolution | 2048 x 1536, 2560 x 1440, 2560 x 1920, 3840 x 2160 |
| Frame Rate | Up-To 25fps, |
| General | |
| Operating Temperature | -10°C ~ 65°C |
| Operating Humidity | 10%-90% RH |
| Power Input | DC 12V ± 10%/POE |
| IR Range | IR Range Up To 25 Mtrs |
| Housing | ABS High Quality Plastic |
| Consumption | Up-To 4 Watt |
| Zoom | Digital Zoom Applicable |
| Light | Warm Array Flood Light |
| Mounting | Wall Mount, Ceiling Mount |
| Features | Human Detection |
| Supported Device | Android, IOS via NVR/DVR |